

EMBEDDED UHF SMD MODULE

M600



PRODUCT DESCRIPTION

The RFID EMBEDDED UHF SMD Module M600 is a high-performance UHF RFID module based on the IMPINJ E310 New Generation reader chip. Manufactured as a surface-mounted device (SMD) with a max. RF output power of 30 dBm and supporting real-time onboard temperature monitoring, this module allows for rapid and seamless integration, especially in PDA and desktop RFID devices.

It is equipped with UHF Technology EPC Class 1 Gen 2 (ISO 18000-63) and is globally applicable with a frequency band of 840 - 960 MHz. The M600 UHF SMD module has a MMCX antenna interface that supports a power output of max 30 dBm, which enables it to rapidly read multi-labels at up to 300 tags per second.

The hardware comes with a useful SDK for the development of controller, Linux or Windows based applications. In addition to the documentation, command protocols and source codes, the SDK includes a Windows-based demo application providing full functionality over all supported UHF RFID standards.

► APPLICATIONS

- Mobile applications
- USB-powered devices
- Short range devices

► FEATURES

- Based on the latest generation Impinj E310 chipset
- EPC C1 GEN2 | ISO 18000-63
- 30 dBm RF power output
- Coin-sized footprint & SMT ready
- UART - TTL

TECHNICAL DATA

RADIO SPECIFICATIONS

Operating Frequency	840...960 MHz, Configurations for USA: 902...928 MHz (FCC), EU: 865...868 MHz (ETSI)
RFID IC	Impinj E310
RF TX Power	+0...30 dBm, adjustable in steps of 1 dB
RF Sensitivity	-73 dBm
Reading Range	Up to 9 meters*
RF Impedance	50 Ω

ELECTRICAL SPECIFICATIONS

Power Supply	3.6...5 Vdc
Power Consumption	850 mA @ +30 dBm TX Power 50 mA Standby 50 µA Power Down Mode
Connectors	Solder Joints
Communication Interface	UART TTL port
Baudrate	9600...921600 bit/s, 115200 bits/s factory default
GPIO	2 Inputs TTL Levels: Logic low: < 0.8 V, minimum 0V Logic high: > 2 V, maximum 3.3 V 2 Outputs TTL Levels: Logic low: maximum 0.4 V Logic high: minimum 2.9V, maximum 3.3V IO: The maximum output current of the port is 5mA

MECHANICAL SPECIFICATIONS

Dimensions	28 × 28 × 4 mm
Weight	10 g
Material	PCB: FR4 Shielding frame: nickel-nickel copper Shield cover: stainless steel

ENVIRONMENTAL CONDITIONS

Operating Temperature	-20 °C ... +55 °C
Storage Temperature	-40 °C ... +85 °C
Humidity	up to 95 %, non-condensing

SUPPORTED STANDARDS / TAGS

ISO Standard	ISO 168000-63 (EPC Class 1 Gen 2)
Read Rate	≥ 300 tags/s
Tag Cache	≥ 1000 Tags @ 12 Bytes EPC size

SDK INFORMATION

Supported OS	Windows, Linux, Android
Supported Languages	C, C#/.NET, Java
Demo Software	Windows

Other functions and details to be continued and upgraded.

ORDER CODES

VERSIONS

EMBEDDED UHF SMD MODULE - TTL

ORDER CODES

S021003UT0